

## KVM4-HDMI-MATRIX

## 4-ports KVM-switch, matrix 4K 60Hz HDMI, 2 x USB 3.2, 4 x USB 2 (HID) med USB-roaming, PIP osv. FEATURES

4-ports KVM-switch/matrix med USB-roaming  
Indgang HDMI 2.0 x 4 (enkelt video x 4 pc'er) / USB 3.2 Gen 1 Type B x 4  
Udgang HDMI 2.0 x 2 (enkelt video x 2 pc'er) / USB 3.2 Gen 1 Type A x 2 (bagside og front)  
4K 4096x2160@60Hz (4:4:4) / 3840x2160@60Hz (4:4:4)  
EDID-styring  
Understøtter 16:9, 21:9, 32:9 skærme  
Vertikal PBP med 2 x 32:9 skalering  
Dobbelt outputtilstand til 2 skærme  
Manuel skift, Skift af genvejstast, Serielle kommandoer  
Musroaming (musemarkøren flytter sig til en anden skærm/pc)  
Lydstikindgang  
Strømforsyning: 9 - 12VDC inkluderet  
Dimensioner: 40 x 220 x 130



## SPECIFICATIONS

|                   |   |                                                                                                                                                                   |
|-------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Serial            | : | RJ11 x 1 ( Baud Rate = 19200bps ) 8-Bands Baud Rate Selections Mini USB x 1 ( Any Baud Rate )                                                                     |
| Driftstemperatur  | : | 0~40°C, Humidity<80%                                                                                                                                              |
| Forsyning         | : | DC 9~12V                                                                                                                                                          |
| Input             | : | HDMI 2.0 x 4 (Single Video x 4 PCs) USB 3.2 Gen 1 Type B x 4 Audio Jack in x 4                                                                                    |
| LED               | : | Status x 1 Port Status LED x 4                                                                                                                                    |
| Modes             | : | Picture by Picture Mode Monitor by Monitor Mode ( Dual Monitor Mode ) (MbM Mode)                                                                                  |
| Output            | : | HDMI 2.0 x 2 (Single Video x 2 PCs) USB 3.2 Gen 1 Type A x 2 (Rear & Front) USB HID Type A x 4 (Rear & Front) Audio Jack out x 1 Audio In x 1 ( Embed to Port A ) |
| Resolution        | : | 4096x2160@60Hz (4:4:4) 3840x2160@60Hz (4:4:4)                                                                                                                     |
| Number of Buttons | : | Port Select x 4 Function x 1 Video Swap x 1 Console Swap x 1 Sync x 1                                                                                             |
| Display           | : | Support 16:9, 21:9, 32:9 Displays                                                                                                                                 |
| Dimensioner       | : | 40 x 220 x 130mm                                                                                                                                                  |

