

Wi-Fi 6 AX1800 Dual Band VPN-sikkerhedsrouter med option PoE+

FEATURES

Næste generations Wi-Fi 6 (802.11ax) med hastigheder på op til 1,8 Gbps
Dual-band (2,4 GHz og 5 GHz) med MU-MIMO til miljøer med høj tæthed
Robuste VPN-funktioner: IPSec, SSL, PPTP, L2TP, GRE (op til 60 tunneler)
Indbygget SPI-firewall, DoS/DDoS-beskyttelse, indholds- og IP-filtrering
Dual-WAN med failover, load balancing og understøttelse af høj tilgængelighed
Central AP-controller med captive portal og RADIUS
Option PoE+ version med 4-port 802.3at PoE og PD Alive Check
Nem implementering via opsætningsguide, dashboard og fjernadministration



SPECIFICATIONS

Driftstemperatur	:	0°C to 50°C; fanless design
Andet	:	Built-in AP controller with captive portal and RADIUS
Firewall	:	SPI Firewall, DoS/DDoS protection, NAT, MAC/IP filtering, Content Filtering, WPA3 support
Porte	:	5 x Gigabit RJ45 (1 WAN, 1 LAN/WAN, 3 LAN)
Standarder	:	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), dual-band 2.4GHz + 5GHz
VPN	:	IPSec, SSL (OpenVPN), PPTP, L2TP, GRE
Material	:	Metal housing, 1U height, desktop or rack-mountable
WiFi	:	Up to 600Mbps (2.4GHz) + 1200Mbps (5GHz)
WWAN	:	Dual-WAN failover, load balancing, high availability

