

Understøtter blæserløs Intel® 14./13./12. generations
Core™ 35W CPU, 2xCOM 8xUSB, 2xLAN, HDMI, DP,
DIN-montering, DC 12~24V

FEATURES

CPU Intel® 14./13./12. Core™ LGA1700-sokkel
(maks. 35 W)
RAM 1 x 262-bens DDR5 SO-DIMM 4800/5600 MHz
SDRAM MAX. 32 GB
Intel® H610E, integreret Intel® UHD-grafik 730/770
1 x 2,5 GbE-porte 2 x GbE-porte (1 x Intel® i226LM,
1 x Intel® i219LM, 1 x Intel® i210AT)
Watchdog-timer
TPM: dTPM 2.0
2xCOM (1x RS232, 1x RS232/422/485)
8x USB (2 x USB-A 3.2 Gen2 (10 Gbps) 2 x USB-A
3.2 Gen1 (5 Gbps) 2 x USB-A 2.0 2 x Intern USB-A
2.0)
1 x M.2 E-nøgle 2230-slot (PCIe 3.0 x1 + USB 2.0 +
CNVi)
1 x mPCIe (PCIe 3.0 x1 + USB 2.0, fuld størrelse)
med 1 x nano-SIM-kortslot
1 x DisplayPort 1.4 (DP++), op til
4096x2304@60Hz
1 x VGA, op til 1920x1200 ved 60Hz
1 x M.2 M-nøgle 2242/2280-slot (PCIe 4.0 x4 +
SATA)
Vægmontering (standard), DIN-skinne (valgfrit med
CTOS-beslag)
-20 ~ 60°C, omgivende temperatur med luftstrøm
CE, FCC Klasse A
Dimensioner (B x D x H) 55 x 164 x 210 mm
DC 12~24V via 2-benet klemrække, maks. 80W
OS-understøttelse: Windows 10 / Windows 11 /
Ubuntu



SPECIFICATIONS

CPU	:	Intel® Core™ i5-13th Gen
CPU	:	Intel® Core™ i3-13th Gen
CPU	:	Intel® Core™ i3-12th Gen
CPU	:	Intel® Core™ i3-14th Gen
CPU	:	Intel® Core™ i5-12th Gen
CPU	:	Intel® Core™ i5-14th Gen
CPU	:	Intel® Core™ i9-12th Gen
CPU	:	Intel® Core™ i9-14th Gen
CPU	:	Intel® Core™ i9-13th Gen
Memory Type	:	DDR5
Max. Memory Capacity	:	32
Storage	:	1 x 2.5" HDD/SSD

SPECIFICATIONS

Graphics	:	Integrated Intel® UHD Graphics 730/770
LAN Chipset	:	1 x Intel® i226
LAN Chipset	:	1 x Intel® i219
LAN Chipset	:	1 x Intel® i210AT
Expansion	:	1 x mPCIe
Expansion	:	1 x nano SIM card slot
Power Input	:	DC 12~24V
Max. Power Consumption	:	170W
Video	:	1 x DisplayPort
Video	:	1x VGA
USB	:	2 x USB-A 2.0

SPECIFICATIONS

Serial	:	1x RS232
Serial	:	1 x RS232/422/485
LAN	:	2x 1Gb LAN
LAN	:	1x 2.5Gb LAN
Driftstemperatur	:	-20 ~ 50°C
Storage Temp.	:	-30 ~ 70°C
Operating Humidity	:	10-95% @ 60°C (non-condensing)
Vibration	:	5~500Hz 3 Grms
Shock	:	10G peak acceleration (11 m sec. duration), operation
Shock	:	30G peak acceleration (11 m sec. duration), nonoperation
Shock	:	According to IEC 68-2-27



EPC-I7G14-2S2L4UDH

SPECIFICATIONS

Dimensions	:	55 x 164 x 210mm
Certification	:	CE/FCC Class A
Antal Video Udgange	:	2
Antal LAN Porte	:	3
Antal USB	:	6
Antal Serial	:	2

