

ETH1SER-B

1 port serielportserver RS232/RS485. Serial Device Server

FEATURES

Serial device server med RS232/RS485
RS232 via DB9
RS485 via skrueterminal - 2-wire



SPECIFICATIONS

CPU	:	16 bit CPU, 100 MHz
Driftstemperatur	:	0 - 50 °C
Hukommelse	:	768 KB RAM, 256 KB ROM
Kabinet	:	Stålkabinet i format 22 x 67 x 93 mm. (H x B x D)
Netværk	:	1 x 10/100 Mbit Ethernet - med autodetektering af hastighed
Porte	:	Én port, der kan bruges som RS232 eller RS485; 1200 bps - 230 Kbps
Protokol	:	TCP, UDP, DHCP, HTTP, ICMP, ARP, ICMP, Telnet
Signaler	:	RS232: Rx, Tx, RTS, CTS, DTR, DSR og DCD. RS485: Data+ og Data- (2-leder halv duplex)
Skærm	:	4 lysdioder viser Tx, Rx, netværks- og systemstatus
Spænding	:	Kræver 9 - 30 VDC maks. 300 mA (ustabiliseret). Netadapter medfølger
Stik	:	DB9-han til RS232. Skrueterminaler til 2-tråds RS485. 1 x RJ45 til Ethernet. Spændingsforsyning: 1 x 5,5 mm. DC jackstik til medfølgende netadapter

