

ETH1SER-K

1 port serielportserver RS232/422/485. Serial Device Server Korenix JETPORT 5601

FEATURES

- Ekstern COM-port over netværkstilslutning
- Serielpport via DB9 male
- 2 x RJ45 netværkstilslutninger



SPECIFICATIONS

Administration	:	Indstilles via netværk over krypteret http (https) vha. enten SSH konsol eller Jetport Commander Windowsprogram
Driftstemperatur	:	-20 ~ 70°C
Andet	:	Seriel porten kan sende data til 5 modtagere simultant. Leveres inkl. 100 ~ 240 VAC adapter, program CD og manualer
Isolation	:	1,5 kV galvanisk isolation
Kompatibilitet	:	COM drivere til WIN10/8/7 (32/64 bit), 2000/ XP/2003 og Vista
Montering	:	DIN skinne monteringsdele og vægbeslag
Netværk	:	2 x 10/100 Mbit Ethernet redundant netværksport, auto fallback less than 200 ms
Porte	:	En port, der kan bruges som RS232, RS422 eller RS485. Hastigheder fra 110 til 460 Kbit/s, Databit:5/6/7/8, Stopbit:1/1,5/2. Paritet: Lige/Ulige/Ingen
Protokol	:	TCP, UDP, Telnet, DHCP, ICMP, https, SSH, BootP, ARP, DNS, SNMP
Stik	:	Seriel port: DB9 hanstik. Ethernet: 2 x RJ45 hunstik
Strømforsyning	:	Redundant spændingsforsyning: 9 ~ 30 VDC via 5.5 mm jack (hun) strømstik. 12 ~ 48 VDC via skrueterminaler
Dimensioner	:	29,6 x 88 x 114,8 (H x B x D)

