

Adlink PCI-7250. 8 kanalers relæ output, 8 kanalers isolerede digitale input, PCI

## FEATURES

- Antal af ind- og udgange kan udvides til 32
- Supports a 32-bit 5 V PCI bus
- 8-CH relay outputs
- 8-CH isolated DI
- On-board LED indicators for relay status
- On-board relay driving circuits
- Relay output stats read back
- On-board low-pass filtering for DI
- Extendable up to 32-CH relay outputs



**SPECIFICATIONS**

|             |   |                                                                                                                                                 |
|-------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Indgang     | : | 8 optoisolerede (PC814). Begge ledere er ført ud for hver indgang<br>ndgangsniveau: Ikke polariseret Logisk 0: 0 - 1,5 VDC Logisk 1: 5 - 24 VDC |
| Isolation   | : | 2.500 VDC                                                                                                                                       |
| Software    | : | Drivere til DOS, Windows 2000, XP, Win7 og Win8 Linux og Labview<br>medfølger                                                                   |
| Stik        | : | DB37 hun                                                                                                                                        |
| Udgange     | : | 8 relæer, 4 slutte (form A), 4 skifte (form C) Belastning: 120 VAC/DC 0,5 A /<br>24 VDC 1 A Skiftetid: Typisk 8 ms                              |
| Dimensioner | : | 107 x 162 mm                                                                                                                                    |

