

2.2 kVA / 1.3 kW UPS for 19" rack mounting, incl. 4 x  
12V / 7Ah batteries, 2U

## FEATURES

- 2200VA, 1350W 2U UPS, 19 "rack mounting
- Simulated sine wave
- During the 3-hour recharge time
- Alarm v. Low battery and overvoltage mm
- Connectors: 6 x IEC ed and 1 x IEC engrave.
- Operating temperature: 0-40 °
- Supports automatic shutdown via software
- Incl. 4 x 12V 7Ah battery



## SPECIFICATIONS

|                  |   |                                                                                                                                                |
|------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Temp.  | : | 0-40 °C                                                                                                                                        |
| Alarm            | : | Bip hvert 3. sekund hvis batteri er aktivt, bip hvert sekund hvis batteriniveau er lavt og kontinuerligt bip ved overspænding                  |
| Batteri          | : | 50 % belastning: 12 min, fuld belastning: 4,5 min                                                                                              |
| Batteri          | : | 4 x 12V 7Ah inkluderet                                                                                                                         |
| Beskyttelse      | : | Mod over- og underspændinger, overbelastning og kortslutning                                                                                   |
| Genopladningstid | : | (90 %) mindre end 3 timer                                                                                                                      |
| Kapacitet        | : | 2200VA / 1350 W                                                                                                                                |
| Montering        | : | 19" rack                                                                                                                                       |
| Software         | : | Der medfølger software, der giver information, om ladestatus, ind- og udgangsspændinger, e-mail advarsel, skemalagt test af UPS og meget mere. |
| Stik             | : | 6 x IEC stik til udgang og 1 x IEC stik til indgang (standard pc spændingsforsyningsstik)                                                      |
| Støj             | : | Under 40 dB (ved 1 meter)                                                                                                                      |
| Weight           | : | 31 kg                                                                                                                                          |



**DANBIT**

UPS2200R

## SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.