

1200 Mbit 2.4 / 5GHz Wireless Wifi Access Point / Bridge / Repeater, Dual Band, IP30 class FEATURES

- Industrielt 2,4/5GHz trådløst Access Point
- 1200Mbps 802.11ac
- Dual Band
- LAN Gigabit Ethernet
- 1 x 10/100/1000BASE-TX RJ45 port med PoE
- 2 x 2.4GHz 5dBi SMA antenne, 2 x 5GHz 5dBi SMA antenne med RP-SMA-stik
- 802.3at PoE, 48-56V DC input
- IP30 tæt kabinet
- Driftstemperatur -10 til +60°
- Til vægmontering



SPECIFICATIONS

Andet	:	Up to 10 multiple-SSIDs (2.4GHz+5GHz) to allow users to access different networks through a single AP. Provides 5-level Transmitting Power Control to adapt various environments.
Antenne	:	Gain: 2 x 2.4GHz 5dBi SMA antenna 2 x 5GHz 5dBi SMA antenna
Forsyning	:	802.3at PoE, 48-56V DC input
Frekvens	:	2.4GHz: America -- FCC: 2.412~2.462GHz Europe -- ETSI: 2.412~2.484GHz 5GHz: America -- FCC: 5.180~5.240GHz, 5.725~5.850GHz Europe -- ETSI: 5.180~5.240GHz
LED	:	PWR Allow LED to turn off via software control
Materiale	:	Metal
Montering	:	Wall Mount
Trådløs	:	Multiple Wireless Modes: AP, Client, WDS PtP/ PtMP, WDS Repeater, Universal Repeater. Supports WMM (Wi-Fi Multimedia) and wireless QoS to enhance the efficiency of multimedia application.
WiFi/WLAN	:	802.11 a/b/g/n/ac
Weight	:	470g
Dimensioner	:	148 x 41 x 140 mm (L x W x H)

