

1 port serial server RS232 / RS422 / RS485. Serial Device Server RJ45, DB9, 9 - 30VDC

FEATURES

- External COM port over Ethernet and Internet RS232/422/485
- Baud rate: 1200 - 230.4kbps (2-wire)
- Max. baud rate at 4-wire RS485 up to 921.6kbps
- Atop SE5201-DB Serial Device Server
- 10/100Mbit Ethernet.
- Serial port via DB9 male connector
- Supports TCP Server/Client, UDP, Virtual COM and Tunneling modes
- Power is supplied from 9 - 30VDC or 5VDC (power jack)
- Power supply not included
- DIN kit (option)
- Dimensions: 65 x 78 x 28mm (without wall bracket)
- Dimensions: 88.5 x 84 x 27.8mm (with wall bracket and DB9 port)



SPECIFICATIONS

Operating Temp.	:	-40°C ~ 70°C
Montering	:	Wall-Mount or DIN-Rail (optional kit)
Netværk	:	10/100 Mbit Ethernet
OS SUPPORT	:	Windows / Linux
Porte	:	RS232 / 422 / 485
Protokol	:	TCP, IPv4, UDP, DHCP Client, HTTP, HTTPS, Telnet, ARP, SNMPv1,v2c,v3
Skærm	:	3 lysdioder viser Tx/Rx, netværks- og systemstatus
Stik	:	3-Pin 5.08mm Lockable Terminal Block, DC Jack (for redundancy), RJ45 10/100 Ethernet, DB9 serial
Strømforbrug	:	Less than 1.5W
Weight	:	185g
Dimensioner	:	65 x 78 x 28mm (without wall-mount part), 88.5 x 84 x 27.8mm (with wall-mount part and DB9 connector)

