

6 x Analog Differential input voltage and to mA. 2 x Analog output voltage and mA, 2 x Dig in 2 x Dig out, 1 x RJ45, PoE

FEATURES

- Built-in Web server
- Web HMI
- Modbus / TCP and Modbus / UDP protocols
- Good communication security
- Dual Watchdog
- Operating temperature range: -25 ~ + 75 ° C
- I/O Pair-link - the input is mirrored in the other's output
- 6 x Analog inputs: 500mV +/- - +/- 10 V, 0 - 20mA (16bit)
- 2 x Analog outputs: 0 - +/- 10VDC, 0 - 20mA (12bit)
- 10 samples per second
- 2 x Digital input (count): Wet / Dry, max. + 30VDC (100Hz)
- 2 x Digital outputs: Open Collector, max. 50VDC / 700mA
- 1 x RJ45 Ethernet
- Power supply: PoE or 10 - 30VDC / 4Watt



SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 4 W via klemrække eller PoE
Indgang	:	6 analoge differentialindgange: ± 500 mV, ± 1 V, ± 5 V, ± 10 V, 0 - 20 mA, 4 - 20 mA, ± 20 mA
Indgang	:	2 stk. Logisk 0: Lagt til stel Logisk 1: Åben
Indgangsimpedans	:	Analog indgange 2 M Ω
Maks. hastighed	:	10 samples/sekund
Netværk	:	10/100 Mbit m/RJ45-stik
Nøjagtighed	:	Mindst ± 0.1 %
Opløsning	:	16 bit
Protokol	:	Modbus/TCP, TCP/IP og UDP
Tæller	:	Digitale Indgange kan virke som 32 bit tæller, maks. frekvens 100 Hz
Udgange	:	2 analoge udgange: 0 - 5 V, 0 - 10V, ± 5 V, ± 10 V 0 - 20 mA, 4 - 20 mA. Opløsning 12 bit, nøjagtighed maks. ± 0.05 %.
Udgange	:	2 stk. "open collector" 30 V/100 mA

