

8 x Digital Inputs Wet 0 - + 50VDC 500Hz, 8 x digital output (OC) + 40VDC 650mA, 2x RJ45, Modbus TCP / UDP, PoE

FEATURES

- Built-in Web server
- Web HMI
- Modbus TCP and Modbus UDP protocols
- Good communication security
- Dual Watchdog
- Operating temperature range: -25 ~ + 75 ° C
- I/O Pair connection - input is mirrored in the other's output
- 8 x Digital input (count): 0 - + 50VDC (500Hz)
- 8 x Digital Outputs: Open Collector 0 - + 40VDC / 650mA per output
- 2 x RJ45 Ethernet - Daisy chain
- Power supply: PoE or 10 - 30VDC / 3watt
- PoE fed NOT proceed to the next module - only data



SPECIFICATIONS

Forsyning	:	10 - 30 VDC, 2 W via klemrække eller PoE
Indgang	:	8 stk. Logisk 0: 0 - 4 VDC, Logisk 1: 10 - 50 VDC
Netværk	:	10/100 Mbit m/RJ45-stik
Protokol	:	Modbus/TCP, TCP/IP og UDP
Switch	:	Indbygget 2 port Ethernet switch
Tæller	:	Indgange kan virke som 32 bit tæller, maks. frekvens 500 Hz
Udgange	:	8 stk. "open collector": 10 - 40VDC / 650 mA (skal forsynes med ekstern forsyningsspænding som strømkilde til de 8 udgange)

