

15" Marine Panel PC i3 9Th Gen. 8GB RAM, 128GB SSD, IP65 front

FEATURES

Marine panel PC

(9th Gen Intel CPU, Windows 10, windows 10 Pro Embedded).

It has 1024 x 768 pixels visible resolution, which is designed and tailored for use in operator display and computer operating systems such as IAS, ICMS, FAMS, AMS, EMS, BWTS, VRCS etc.

MIL Qualified Product from Military test rules

Anti-Glare and Anti-Reflective TFT LCD Technology

LED Backlight Technology

Tempered Glass for Panel Protection

Long-Term Lifecycle Management



SPECIFICATIONS

CPU	:	Intel Core i3 2310M 2.5GHz CPU
Chipset	:	Intel QM67
Chipset	:	Intel® H310 Express Chipset
USB	:	2 x USB 2.0 Front, 4 x USB 3.2 Rear
Serial	:	2 x Com (COM1: RS-232/422/485, COM2: RS-232 Only) 1 x Com (Com3: RS-422/485, Terminal Block)
Operating Temp.	:	0° til 60° C
Operating Temp.	:	Temperature - Operation 0-70°C, Storage -30-70°C
Drev	:	1 x 2.5" SATA harddisk eller SSD Monteret med 128GB SSD Harddisk
Hukommelse	:	2 x 204-pin DDR3 SO-DIMM Maks. 8 GB Monteret med 4GB RAM
IP-Tæthed	:	IP 65 Front
Kabinet	:	Stålkabinet og IP65 tæthed i fronten
Kontrast	:	1000:1



SPECIFICATIONS

Mål og vægt	:	5.55 kg
Netværk	:	1 x Intel 82579L 10/100/1000 Mbit Ethernet m/RJ45-stik 1 x Realtek RTL811C 10/100/1000 Mbit Ethernet m/RJ45-stik
Netværk	:	2 x Realtek® PCIe Gb LAN RTL8111H
OS SUPPORT	:	Understøtter Windows XP, 7/8 embedded 7 samt Server 2008. Linux Ubuntu 10.x
OS SUPPORT	:	Windows 10 Pro Embedded
Porte	:	1 x RS232, 1 x RS232/422/485 alle med DB9 hanstik
Skærm	:	15" TFT, 1024 x 768 resistive touch
SSD	:	128GB
Strømforsyning	:	Indbygget 100-240VAC strømforsyning
Synsfelt	:	304.128 H x 228.096 V mm
Tastatur/mus	:	Via USB porte



SPECIFICATIONS

Display	:	15" XGA Color TFT LCD
brightness	:	350 cd/m ²
Dimensioner	:	330 x 402 x 80 mm
Dimensioner	:	402W x 331.5H x 83.3D mm
Certification	:	ABS, DNV, KR, LR, IEC 60945

