

PCI Express card for USB 3.1C. PCIE card with USB3.1C

FEATURES

PCI Express Base Specification Revision 3.0 single lane (x1).

Compliant with the Universal Serial Bus 3.1 specification Gen2.

Compliant with xHCI (eXtensible Host Controller Interface) specifications Revision 1.1

Supports simultaneous operation of multiple USB 3.1, 3.0, USB 2.0 and USB 1.1 devices

Supports USB data transfer rate of 10G/5G/480/12/1.5Mbps.

Expands a single external USB 3.1 Super Speed plus Type-C port (DFP) on the system.

The USB port provides a maximum of +5V DC / 3000mA power output to USB device.

Built-in overcurrent protection on each USB port. Supports the device's remote wake-up function from USB keyboard or mouse.

The hot swapping feature allows you to connect/disconnect a device without turning off the system.

Driver support for Microsoft Windows 7, 8.x and 10 operating systems

Certified with electromagnetic compatibility CE, FCC, VCCI, C Tick, BSMI and RoHS approval.

Windows 11 64bit

Windows 10 32/64 bit

Windows 8.1 32/64 bit

Windows 8.0 32/64 bit

Windows Server 2022 64bit

Windows Server 2019 64bit

Windows Server 2016 64bit

Windows Server 2012 R2 64-bit

Windows Server 2012 64bit



**DANBIT****CNV-PCIE-USB3.1C**

SPECIFICATIONS

OS SUPPORT	:	Windows 7, 8, 10. Linux 2.6.31 eller nyere
Porte	:	1x USB 3.1C



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.