

Compact Embedded PC Bay Trail 1.91GHz, 2 x POE Ethernet, POC-200, Fanless EOL

FEATURES

- Ultra compact 150mm x 100mm
- Intel® Atom™ E3845 1.91 GHz Quad-core
- Fanless
- 2 x 802.3at (25.5W) Gigabit PoE ports
- 3 x USB 3.0
- 2.5" SATA HDD/SSD
- Option: built-in eMMC
- Up to two RS-232/422/485 ports and two RS-232 ports
- 25°C to 70°C
- 8~35VDC
- The product is EOL, only those in stock
- Replacement EPC-N4200-DIN+



SPECIFICATIONS

CPU	:	1.91GHz Intel® Atom™ E3845 Quad-core processor
USB	:	3x USB 3.0 ports and 1x USB 2.0 port
Operating Temp.	:	-25°C ~ 70°C with SSD , 100% CPU loading */** -10°C ~ 50°C with HDD, 100% CPU loading */**
Chok/Vibration	:	Vibration Operating, 5 Grms, 5-500 Hz, 3 Axes(w/ SSD, according to IEC60068-2-64) Shock Operating, 50 Grms, Half-sine 11 ms Duration (w/ SSD, according to IEC60068-2-27)
Ethernet	:	2x Gigabit Ethernet ports by Intel® PoE IEEE 802.3at (25.5W PSE)
Forsyning	:	Built-in 8~35V DC Input Connector 1x 2-pin pluggable terminal block for DC input
Grafik	:	Integrated Intel® HD Graphics
Harddisk	:	1x SATA ports with 2.5" HDD/SSD
Hukommelse	:	1x SO-DIMM socket for DDR3L-1333, without
I/O	:	4-CH isolated DI + 4-CH isolated DO
Montering	:	Wall-mounting (standard) or DIN-Rail mounting (optional)
Porte	:	2x RS-232/422/485, 2x RS-232



SPECIFICATIONS

Udgange	:	1x DVI-I connector for both analog RGB and DVI/HDMI outputs
Udvidelser	:	1x mini PCI Express slot with USIM socket
Weight	:	1.1 kg (including one 2.5" HDD)
Dimensioner	:	149mm (W) x 105 mm (H) x 57 mm (D)

