

MOD485-DA8-I

8 analog outputs 0-5V, 0-10V, 0-20mA, 12bit, RS485,
MODBUS, 10-30VDC

FEATURES

- 8 channel analog output module, Modbus protocol
- Source type power output
- 8 x 12-bit analog outputs
- Individual Channel Configuration
- Cable Break Detection at 4-20mA
- 8kV ESD Protection
- Power-on Value Programming
- Security Value Programming
- Temperature -25 to +75°C



SPECIFICATIONS

Operating Temp.	:	-25 ... 75 °C
Andet	:	+/-35 VDC Overvoltage Protection
Baudrate	:	1200 to 115200 bps
Indgangsimpedans	:	500 Ω
Installation	:	DIN-Rail or Wall Mounting
Interface	:	RS485
Isolation	:	3000 VDC
Luftfugtighed	:	10 to 95% RH, Non-condensing
Opløsning	:	12-bit
Output	:	+10 ~ +30 VDC
Protokol	:	Modbus RTU, DCON
Udgange	:	0 ~+5 VDC $\pm$ 5 VDC 0 ~ +10 VDC $\pm$ 10 VDC 0 ~ +20 mA +4 ~ +20 mA



**DANBIT**

MOD485-DA8-I

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.