

Industriel BOX PC med 2 x PCIe udvidelse. Intel i7/i5/i3 Haswell

FEATURES

- Fanless Design
- Wide Range DC Power Input (9~36V)
- iAMT supported
- Triple Independent Displays (DVI-I + DisplayPort*2) supported
- Optional WiFi or HSUPA Wireless Connectivity supported
- Rugged Design for Shock / Vibration Protection
- Memory Support up to 16GB (DDR3)
- RAID 0,1 Supported
- 3xGbit



SPECIFICATIONS

CPU	:	4th Generation Intel® Core™ i7/i5/i3 or Haswell Processor in LGA1150 socket
Storage	:	2 x 2.5" drive bays 1 x outside accessible CFast socket
Chipset	:	Intel® Q87
USB	:	6 x USB 3.0/ 2.0 ports Internal USB dongle (Optional)
Operating Temp.	:	-20 ~ 55°C (-4 ~ 131°F), ambient w/ air flow
Chok/Vibration	:	Vibration 3 Grms/5~500Hz/random operation w/ SSD Shock Operating 40G (11ms), Non-operating 60G with SSD
Forsyning	:	DC 9~36V input w/ 4-pin terminal block
Grafik	:	Integrated Intel® HD 4600 2 x DisplayPort female connector for Digital Video output 1 x DVI-I female connector for Digital/Analog Video output
Hukommelse	:	2 x 204-pin DDR3 SO-DIMM sockets, supporting 1600MHz SDRAM up to 16GB
I/O	:	1 x DB25 connector for 1 x DIO (8 in/8 out) port or 1 x LPT port (either one) DIO by default, can be changed to LPT
Ledige Slots	:	1 x PCIe x 16 slot 1 x PCIe x8 slot (via x 4 lanes)
Luftfugtighed	:	10 ~ 95% @ 55°C (non-condensing)



SPECIFICATIONS

Montering	:	Wall-mount
Netværk	:	3 x RJ45, 1 x Intel® i217LM GbE PHY w/ iAMT 2 x Intel® i210IT GbE
OS SUPPORT	:	W7 Pro / WS7E / WE8 STD
Porte	:	COM1/ COM2 RS-232/422/485 Selectable COM3/COM4 RS-232
SATA	:	2 x Serial ATA ports with RAID 0/1 support
Strømforbrug	:	Max.75W(w/o I/O Card)
Watchdog	:	1~255 levels reset
Weight	:	7 kg (15.43 lb)
Dimensioner	:	225 x 267 x 120 mm

