

## 10.4" Panel PC godkendt til Tog brug, (EN 50155 for railway)

### FEATURES

- Sunlight readable 10.4"
- 1000 Nits
- Auto-dimming
- 25°C to +70°C
- EN 50155 certified for railway



## SPECIFICATIONS

|                 |   |                                                                                                                       |
|-----------------|---|-----------------------------------------------------------------------------------------------------------------------|
| Storage         | : | 16GB flash onboard                                                                                                    |
| Chipset         | : | SoC Integrated                                                                                                        |
| USB             | : | 2 x USB 2.0 (M12, A-coded)                                                                                            |
| Operating Temp. | : | -25°C ~ +70°C (-13°F ~ +158°F)                                                                                        |
| Andet           | : | 1 x isolated CAN bus 1 x isolated DIO (6-IN/2OUT) (phoenix type) 1 x isolated DC for power input (M12, A-coded)       |
| Approval        | : | EN 50155, EN 50121-3-2 EMC, EN 61373 (Shock/Vibration), EN 45545 (fire) certified Compliance with UIC 612-01 (keypad) |
| Ethernet        | : | 2 x isolated 10/100/1000Mbps (M12, X-coded)                                                                           |
| Forsyning       | : | 16.8V to 30V DC or 77V to 137.5 VDC 10ms hold up time (S2) Power Consumpt                                             |
| Hukommelse      | : | DDR3 4 GB (default) or 8 GB memory onboard                                                                            |
| IP-Tæthed       | : | Front Bezel IP65, NEMA 4 rugged protection, aluminum front bezel                                                      |
| Lyd             | : | Line out/Line in/speaker out                                                                                          |
| Montering       | : | Suspension mount VESA mount                                                                                           |



## SPECIFICATIONS

|             |   |                                                       |
|-------------|---|-------------------------------------------------------|
| OS SUPPORT  | : | Windows® 10, Windows® 8/8.1, WES 8, Windows® 7, WES 7 |
| Porte       | : | 2 x isolated RS-232/422/485 (M12, A-coded)            |
| Skærm       | : | 10.4" SVGA TFT LCD 1000 nits 800 x 600 pixels         |
| Touch       | : | 5-wire resistive touch panel                          |
| Udvidelser  | : | 2 x PCI Express Mini Card                             |
| Watchdog    | : | 255 levels, 1 ~ 255 sec.                              |
| Weight      | : | 2.4 kg (5.29 lb) / 5 kg (11.02 lb)                    |
| Dimensioner | : | 310 x 65.05 x 216 mm (12.20" x 2.56" x 8.50")         |

