

ESW4SFP2

4 Ports 10/100 / 1000Mbit RJ45 + 2 Ports 100 / 1000Mbit SFP Slot, Managed Switch, 12 - 48VDC and 24Vac

FEATURES

- Real Ring, Redundant Ring of critical network
- IEEE 1588 Time Protocol, supports MEF service and synchronous Ethernet
- Supports MODBUS TCP protocol
- Supports IGMP Snooping to 4 x 10/100 / 1000Mbps RJ45 ports
- 2 x 100 / 1000Mbit SFP ports
- 12 - 48VDC, redundant input
- 24VAC supply voltage is also possible
- IP30 metal housing with DIN bracket
- temperature range from -40 to + 75 ° C



SPECIFICATIONS

Operating Temp.	:	-40 - 75°
Forsyning	:	Dual 12~48V DC 24V AC
Materiale	:	IP30 metal case
Montering	:	DIN rail kit and wall-mount kit
Porte	:	4 10/100/1000BASE-T RJ45 auto-MDI/MDI-X ports
Slot	:	2 1000BASE-SX/LX/BX SFP interfaces (Port-5 to Port-6) Compatible with 100BASE-FX SFP
Stik	:	Removable 6-pin terminal block for power input Pin 1/2 for Power 1, Pin 3/4 for fault alarm, Pin 5/6 for Power 2
VLAN	:	802.1Q tagged based VLAN, up to 255 VLAN groups Q-in-Q tunneling Private VLAN Edge (PVE) MAC-based VLAN Protocol-based VLAN Voice VLAN MVR (Multicast VLAN Registration) Up to 255 VLAN groups, out of 4094 VLAN IDs
Dimensioner	:	32 x 87x 135 mm

