

MON-MAR19A

19" TFT, marine approved panel monitor with IP65 tightness, without touch

FEATURES

FEATURES

19 "TFT Marine Monitor With IP65, No Touch
LED Backlight
250 Nits
1 x HDMI, 1 x VGA, 1 x Composite, 1 x Audio3.5
Jack Connector
Anti- Vibration: 5 - 500 Hz / 1 Grms PTP
Anti Schock: 15G / Peak (11ms)
AC Power Standard IEC Inlet 100-240V AC
Power On / Off Via Front Buttons
VR Brightness Knob Adjustment
Power Mode Status LED Indicator
On Screen Display Control (OSD)
Flush Mount, VESA Mount
Optional: AR Hardness Glass: 3mm Anti-Reflective
Protect Glass
Optional: DC Power: Isolate 12V / 24V / 48V / 125V
DC Power
Optional: SR-BKT: Stand & Roof Mounting Bracket
Optional: RT-BKT: Rotary Plate Rugged Bracket
Optional: SV-BKT: Sun-Visor bracket



SPECIFICATIONS

Operating Temp.	: 0 - 50 deg. C
I/O	: 1 x HDMI, 1 x VGA, 1 x Composite (RCA), 1 x 3.5" jack audio
IP-Tæthed	: IP65 tæthed
Kontrast	: 1000:1, 250 cd/m2
Compositions	: Alminum Front Bezel + Metal Housing
Montering	: Panel (Flush) Mount, VESA Mount, Robust Bracket, Sun-visor Bracket
Strømforsyning	: AC standard IEC inlet
Weight	: 9.5 / 13 KGs
Dimensioner	: fysiske dimensioner: 483 x 444 x 70mm. pakke: 620 x 580 x 220mm
Certifications	: CE / FCC / RoHs / IEC60945

