

6 x Power relay, 6 x digital input over Ethernet
Modbus/TCP 1 x RJ45, PoE or 12 - 48VDC

FEATURES

Modbus TCP Slave Module LAN or Internet

6 x Relay, End Contact 250VAC / 5A, 30VDC / 5A
Avoid inductive load

6 x Digital input. High is 10 - 50V
supply via PoE or 12 - 48VDC

is with I / O Pair Connection - Input is mirrored to
exit.

with important "Safe Setting" which sets relays as
desired

watchdog which sets relays in "Safe Setting" in
error detection

Dim: 123 x 72 x 35 mm

built-in your bracket



SPECIFICATIONS

Forsyning	:	12 - 48 VDC 2 W eller PoE
Indgang	:	6 stk. isolerede med fælles stel Logisk 0: 0 - 4 V Logisk 1: 10 - 50 V
Isolation	:	3750 VDC
Konfiguration	:	Via webbrowser
Stik	:	Skrueterminaler
Udgange	:	6 relæer Type A (slutte) Belastning: 30 VDC / 5A maks. pr. kanal 250 VAC / 5A maks. pr. kanal
Watchdog	:	2 stk. Watchdog timer. Den ene bruges til at genstarte modulet, hvis det fryser/låser. Den anden kan sætte udgangene til en forud bestemt værdi ved kommunikationsfejl
Dimensioner	:	123 mm x 72 mm x 35 mm

