

12.1 "LCD touch monitor, readable in bright sunlight, IP65 front, VGA, 4: 3 format

FEATURES

12.1 "LCD Monitor

IP65 close front
Resolution 1024 x 768, 4: 3 format
800: 1
1 x VGA interface to 5-wire resistive touch screen
300 nits
12V DC input
input: 110 - 240V
Output: 12VDC
Operating temperature: -20 - 70C VESA Church and
panel mounting
Optional: 1000 nits Optional
: DVI
Optional: Display Port
Optional: USB for touch
Optional: HDMI Kabel



SPECIFICATIONS

Operating Temp.	:	0-50°C
Antal farver	:	16.2M (8 bits / color)
Betragningsvinkel	:	Viewing Angle : -80 ~ 80 (H); -70 ~ 70(V)
Forsyning	:	Power Adapter : 1 x ext. 100~220V AC to DC 12V adapter
Interface	:	1 x VGA D-Sub 15 pin
Kontrast	:	Contrast Ratio : 800 : 1 (typ.)
Lysstyrke	:	Brightness : 500 nits (cd/m2)
Montering	:	VESA DPMS compliant
Opløsning	:	1024 x 768 @ 60Hz, 75Hz
OSD	:	OSD Input : 5-key OSD buttons • OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings
Pixels	:	0.24(H) x 0.24(V)
Skærm	:	12.1" LCD



**DANBIT**

MON12-LPM-RHB

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.