

USB to CAN bus converter, isolated FEATURES

- Konverter fra USB til CAN bus
- Tilsluttes via USB
- Supporterer CAN 2.0A / 2.0B, op til 1 Mbit/s
- Drivers til Windows, Linux and Mac OS X
- 16kV ESD surge protection
- 2.5kV isolation
- Til væg eller DIN skinne montering



SPECIFICATIONS

Operating Temp.	:	–25°C - 75°C
Forsyning	:	Via Input Voltage 5V (USB) Power Consumption max 80mA @ 5V, 400mW Connector USB Type B, bus powered, no external supply
Interface	:	USB 2.0 Full Speed, USB 1.1 compliant
Isolation	:	16kV ESD surge protection 2.5kV Electrical isolation
Materiale	:	0.8mm sheet metal
Montering	:	DIN-Rail (optional) Wall mount
OS SUPPORT	:	Windows 2000 up to Windows 10 Windows Server 2000 up to 2012 Linux kernel 2.6+ Mac OS X support available
Stik	:	DB 9 han stik til CAN bus. USB type B hun stik
Weight	:	w/o box 150g; w/h box 200g
Dimensioner	:	50×72×22 mm (W×L×H) Case 72×72×22 mm (W×L×H) with mounting wings

