

MOD485-R12-I

12 x Power Relay Module to 30VDC 5A 250VAC 5A,
RS485 bus, MODBUS / RTU / DCON, 10 - 30VDC
2.5watt

FEATURES

- 12 channel power relay output module
- RS485 to MODBUS
- Communicates via MODBUS RTU
- Operating temperature -25 ° -75 ° C
- 4 kV EFT protection
- 3 kV Surge Protection
- for wall or DIN rail mounting



SPECIFICATIONS

Operating Temp.	: -25 ~ +75°C
Baudrate	: 1200 ~ 115200 bps
Beskyttelse	: EFT: ±4 kV for Power Line, Surge: ±3 kV for Power Line
Forsyning	: Input Range 10 ~ 30 VDC, Consumption: 1.7 W- 2.3 W
Interface	: RS-485
Isolation	: 3750 VDC
LED	: Yes, 12 LEDs as Digital Input/ Relay Output Indicators
Montering	: DIN-Rail or Wall Mounting
Protokol	: Modbus RTU, DCON
Relæ	: 12 (Form A) power relay, Rating: 5 A @ 250 VAC 5 A @ 30 VDC, Load 10 mA @ 5 V
Watchdog	: Yes, Module (1.6 Seconds), Communication (Programmable)
Dimensioner	: 72 mm x 123 mm x 35 mm

