

6 kVA / 5.4 kW Professional Online UPS for 19" Rack / Tower, including battery bank. When safety must be at the top

## FEATURES

6.0 kVA / 5.4 kW UPS inkl. batterier  
UPS 6000VA 5400W, 176-300VAC  
Model 230V: +/- 10%, 50Hz (+/- 0.1%), 2 - 6 ms typical, Simulated Sinewave  
Alarm: UPS Status, ladeniveau, batteriniveau, Input/Output, afladning og fejl indikator  
Dimensioner: 580mm (D) x 438mm (W) x 133mm (H) (3U)  
Til 19" rackmontage  
Vægt: 17 kg



## SPECIFICATIONS

|               |   |                                                                                                                                                                                                                                        |
|---------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alarm         | : | Battery Mode Sounding every 4 seconds Low Battery Sounding every second Overload Sounding twice every second Fault Continuously sounding                                                                                               |
| Andet         | : | Single Phase with ground                                                                                                                                                                                                               |
| Batteri       | : | Battery Type / Numbers Battery Pack Voltage: 240 V Nukbers depending on the capacity of external batteries Charging Current (max.) 4.0 A Charging Voltage 273 VDC                                                                      |
| Input         | : | Voltage Range 176-300 VAC at 100% load 110-300 VAC at 75% load Frequency Range 46Hz - 54Hz or 56Hz - 64Hz Power Factor $\geq 0.99$ @ Nominal Voltage (100% Load)                                                                       |
| Kapacitet     | : | 6.0 kVA / 5.4 kW                                                                                                                                                                                                                       |
| LED           | : | UPS Status, Load Level, Battery level, Input/Output Voltage, Discharge Timer and Fault conditions                                                                                                                                      |
| Montering     | : | 19" rack                                                                                                                                                                                                                               |
| OS SUPPORT    | : | Supports Windows 2000/2003/XP/Vista/2008/7/8, Linux, Unix, and MAC                                                                                                                                                                     |
| Output        | : | Output Voltage 200/208/220/230/240 VAC Voltage Regulation $\pm 1\%$ Frequency range (Synchronized Range) 46Hz - 54Hz or 56Hz - 64Hz Frequency Range (Batt. Mode) 50Hz $\pm 0.1$ Hz or 60Hz $\pm 0.1$ Hz Current Crest Ratio 3:1 (max.) |
| Spændingsform | : | Pure Sinewave                                                                                                                                                                                                                          |
| Stik          | : | AC Input Connector Terminal AC Output Connector Terminal                                                                                                                                                                               |
| Støj          | : | Less than 58dBa @ 1 Meter                                                                                                                                                                                                              |



**DANBIT**

UPS-6KVA-RED

## SPECIFICATIONS

Dimensioner : 580mm (D) x 438mm (W) x 133mm (H) (3U)



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.