

19 "SXGA TFT Panel PC 6. Gen i3 / i5 / i7, Celeron & Pentium, Option: 1 PCI or PCIe slot

FEATURES

- 19 "SXGA TFT LCD
- 1280 x 1024 Pixels
- 2x288 pin DIMM DDR4-2133 max. 32GB
- 3xRS232, 1xRS232 / 422/485
- 4xUSB 3.0, 2 x USB 2.0
- 2 x Ethernet 10/100 / 1Gbit
- 1xHDMI, 1xVGA, 1X DP
- IP65 front
- Audio
- Option: 1PClex or 1PCI
- DVD option
- WIN 10 support



Front USB ports

▲ Optional ODD Drive



SPECIFICATIONS

CPU	:	Socket LGA 1151 6. gen i3/i5/i7, Celeron & Pentium processors
Storage	:	1 x 3.5SATA HDD or 1 x 2½" SATA HDD
Chipset	:	Intel H110
USB	:	4 x USB 3.0 (back), 2 x USB 2.0 (front)
Operating Temp.	:	0C ~45C
Andet	:	Slim DVD as option, 1 x PS/2 keyboard & mouse combo
Approval	:	CE
Chok/Vibration	:	1.0G, 5-500Hz, random
Ethernet	:	2 x 10/100/1000 Mps (intel i219LM/i211AT)
Hukommelse	:	2 x 288 pin long DIMM DDR4-2133 max. 32 GB
Luftfugtighed	:	10% to 90% non condensing
Lyd	:	Mic-in/Line-out



SPECIFICATIONS

Montering	:	VESA, WALL, RACK
OS SUPPORT	:	WIN 10
Porte	:	3 x RS232, 1 x RS232/422/485
Skærm	:	19" SXGA TFT LCD, 250Nits, 1280 x 1024 Pixels
Strømforbrug	:	157W
Strømforsyning	:	100 ~ 240 Vac, 270W
Touch	:	5-wire Resistive
Udgange	:	1 x HDMI, 1 x VGA, 1 x Display port
Udvidelser	:	1 x PCIe or 1 x PCI, when ordering
Watchdog	:	255 levels, 1~255 sec.
Weight	:	8 Kg / 10.4 Kg





DANBIT

IPP19IX-PCIEX

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.