

24 ports Industrial 10/100 / 1000Mbit + 4 x 100 / 1000Mbit SFP, combi, managed PoE switch. Rack. -40 - + 75 ° C, 46 - 57VDC

## FEATURES

24 x 10/100 / 1000Tx IEEE 802.3 Off / On, PoE + Gigabit Ports (30W / Port) + 4 x Gigabit Copper / SFP Combi Ports  
4 x 10/100 / 1000Tx RJ45 + 4 x 100/1000 SFP Slots  
Management: SNMP v1 / v2c / v3, WEB, Telnet, Standard MIB  
Security: 802.1x (Port Based, MD5 / TLS / TTLS / PEAP Encryption), HTTPS, SSH and SNMPv3  
Redundant : Proprietary Ring (Ultra-High-Speed Recovery Time <20 ms), RSTP / STP (802.1w / 1D), MSTP  
48VDC Power Input (46-57 VDC for PoE off, 53-57 VDC recommended for PoE at) 2 Relay Outputs  
Temperature: -40 ° - 75 ° C - Polarity Protection  
Overload Protector  
1U Rack Mount Design  
IP30 Close



## SPECIFICATIONS

|                 |   |                                                               |
|-----------------|---|---------------------------------------------------------------|
| Operating Temp. | : | -40 - +75                                                     |
| Fiber           | : | 4 x 100/1000Mbps SFP slot                                     |
| Forsyning       | : | 46 - 57VDC, redundant                                         |
| Kabinet         | : | 1U, 19" rack, metal, IP30                                     |
| Maks. effekt    | : | 20 Watt system, 30 Watt per PoE port, maks. 480 Watt          |
| Netværk         | : | 24 x 10/100/1000Mbps, RJ45, PoE+                              |
| Protokol        | : | IGMP, SNMP, TFTP, SNMP, SMTP, Syslog, Web-browser, Ring, IPv6 |
| Dimensioner     | : | 438 x 43,6 x 259,2mm, 1U, rack                                |

