

HDMI 4K Extender over LAN and Direct with PoE, Receiver Module, with USB

FEATURES

- 4K HDMI/USB video receiver PoE over LAN
- Suitable for Video wall
- Use Multi casting switch (IGMP Snooping)
- 1080p or 4K (3840 x 2160) HDMI resolution
- HDMI 1.4a - approx. 0.1 second delay between transmitter and receiver
- 1 x RJ45, 1 x DB-9 female, 1 x HDMI female
- 4 x USB 2.0 type A (mouse/keyboard/USB touch)
- Can be fitted up to 8 x 16 video wall
- Transmitter/receiver selector - 16 channels (DIP)
- Supply: IEEE 802.3af/at PoE+; 12V DC 3A (not included)
- Range up to 100m over direct Cat. 5e/6 UTP cables
- EDID emulation and IR transfer
- As transmitter, use HDMI-MULTI4K-T



SPECIFICATIONS

Video	:	Visual lossless compression
USB	:	USB 2.0 type A x 4 (For mouse/keyboard)
Operating Temp.	:	0-55°
Andet	:	EDID (Extended Display Identification Data) function
Båndbredde	:	Approximately 275Mbps@ 4K 30Hz
Forsyning	:	IEEE 802.3af/at PoE+ 12V DC, 2A
HDMI	:	HDMI 1.4a
Kabel	:	Cat5e/6 UTP cable
Kanaler	:	DIP (16 channels)
LED	:	ACT LED x 1 Link LED x 1
Lyd	:	HDMI: 2-ch uncompressed audio
Opløsning	:	HDMI Video:4K (3840x2160) @ 30/24 Hz 1080p @ 60/50 Hz 1080p @ 30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz VGA Video:1080p @ 30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz



SPECIFICATIONS

Protokol	:	TCP, UDP, RTSP, RTP, DHCP, IGMP Snooping, Multicast, IPv4
Rækkevidde	:	100 meters (330 feet) over CAT5e/6 cable
Sikkerhed	:	HDCP compliant
Standarder	:	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3af/at PoE+
Weight	:	620 g
Dimensioner	:	194 x 114 x 28 mm

