

HD HDMI extender over IP med PoE - Digital Signage, sendermodul

FEATURES

- HDMI video transmitter PoE
- Suitable for video wall
- With HDMI Loop Out
- Delay of approx. 1 second from transmitter to receiver
- HDMI 1.4a - H.264
- By IP multicast use switch with IGMP Snooping
- Range up to 100m
- Cables Kat. 5th / 6
- EDID Emulation
- IR Transfer
- 1 x RJ45, 1 x DB-9, 1 x HDMI Input, 1 x HDMI Output
- Supply IEEE 802.3af / at PoE +; 5V DC, 2A (not supplied)
- As receiver, use HDMI-MULTI-HD-M



SPECIFICATIONS

Video	:	H.264 format for video encoder/decoder. MPEG 1 Layer II format for audio encoder/decoder
Operating Temp.	:	0-50°
Andet	:	EDID (Extended Display Identification Data) function
Båndbredde	:	15Mbps (max.)
Forsyning	:	IEEE 802.3af/at PoE+ 5V DC, 2A
HDMI	:	HDMI 1.4a
Kabel	:	Cat5e/6 UTP cable
Kanaler	:	DIP (64 channels)
Lyd	:	2-ch uncompressed audio
Opløsning	:	Video In Resolution: 1080p @ 60/50 Hz 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz Video Out Resolution: 1080p @30/25 Hz 1080i @ 60/50 Hz 720p @ 60/50 Hz 480p @ 60/50 Hz 480i @ 60/50 Hz
Porte	:	RJ45, 1 DB-9, 1 HDMI In, 1 HDMI Out
Protokol	:	TCP, UDP, RTSP, RTP, DHCP, IGMP Snooping, Multicast, IPv4

SPECIFICATIONS

Sikkerhed	:	HDCP compliant
Standarder	:	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3af/at PoE+
Weight	:	290 g
Dimensioner	:	130 x 82 x 30.25 mm

