


1 x RJ45 PCIe Broadcom BCM95761A6110G (based on the BCM5761 chip), 10/100/1000 Mbps (Gigabit Ethernet)

FEATURES

- Chipset: Broadcom BCM5761
- Interface: PCI Express x1 (some versions use x4 or x8)
- Network speed: 10/100/1000 Mbps (Gigabit Ethernet)
- Port type: 1 x RJ45 (copper)
- Controller: NetXtreme Gigabit Ethernet controller
- Supported features: PXE boot (Preboot Execution Environment), Wake-on-LAN (WoL)
- TCP/UDP/IP checksum offload
- VLAN tagging (802.1Q)
- MSI-X support (Message Signaled Interrupts)
- ACPI (Advanced Configuration and Power Interface)
- Drivers available for:
 - Windows Server
 - Linux (via kernel or Broadcom driver)
 - VMware ESXi (depending on version)



SPECIFICATIONS

Andet	:	Compatible with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab Supports Wake On LAN (WOL) Supports IEEE 802.3x full duplex flow control • Supports IEEE 802.1Q Virtual LAN (VLAN)
Hastighed	:	Ethernet up to 10 Mb/s (Half/Full Duplex) Fast Ethernet up to 100 Mb/s (Half/Full Duplex) Gigabit Ethernet up to 1000 Mb/s (Half/Full Duplex) PCI Express x1 up to 2.5 Gb/s
OS SUPPORT	:	Windows Server-2003/Server-2008/Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64/10/10-64, Mac OS 10.5, 10.6, 10.7, Linux Kernel 3.4
Stik	:	external: 2 x Gigabit LAN RJ45 female internal: 1 x PCI Express x1, V1.1

