

4 x isolated digital input (counter) and 4 x relay output - DCON and Modbus RTU -25 ~ +75°C FEATURES

- 4 x Digital input and 4 x relay output
- Form A and Form C Power relay
- Source and Sink type of D/I
- D/I the entries is also 16-bit counter
- Configurable Power-on settings
- Configurable Safe Value setting
- Dual Watchdog
- Temperature range -25 to + 75 ° C
- Supply voltage: 10 - 30VDC
- DIN bracket



SPECIFICATIONS

Operating Temp.	: -25 - +75 °C
Baudrate	: 1200 ~ 115200 bps
ESD	: ±4 kV Contact for each Terminal ±8 kV Air for Random Point
Forsyning	: 10 ~ 30 VDC, 1.4 W
Indgang	: 4 x Digital input
Indgangsimpedans	: 10 kΩ
Interface	: RS-485 Modbus RTU, DCON
Isolation	: Intra-Module Isolation, Field-to-Logic 3750 VDC
LED	: 1 xLED as Power/Communication Indicator. I/O LED Indicators: 8 LEDs as Digital Input/Relay Output Indicators
Montering	: Wall, DIN-Rail mount
Protokol	: Modbus RTU: Slave, DCON: Slave
Stik	: Screw Terminal



SPECIFICATIONS

Udgange	:	Digital output 4 x Electromagnetic relay
Watchdog	:	Yes
Dimensioner	:	72 mm (W) x 123 mm (H) x 35 mm (D)

