

M485-CNV4RS232

Addressable RS485 Convert to 3 x RS232, 1 x RS485 /  
422 port. Up to 115.2 Baud, -25 - +75°C

## FEATURES

- RS485 & recoverable RS232 controller / converter
- Link to 3 x RS232 units from 1 x RS485 bus
- Baud speed 300 bit/s to 115,200 bit/s
- 10 V DC to + 30 V DC
- Dual watchdog
- 256 KB SRAM buffer
- 1 x RS485 address per. serial interface
- Operating temperature: -25 ° to + 75 ° C
- For DIN rail mounting



## SPECIFICATIONS

|                 |   |                                                                                                            |
|-----------------|---|------------------------------------------------------------------------------------------------------------|
| Operating Temp. | : | -25°C to +75°C                                                                                             |
| Andet           | : | Self-tuner ASIC inside For RS-485 COM2 , COM1                                                              |
| Beskyttelse     | : | Power reverse polarity protection                                                                          |
| Forsyning       | : | 10 - 30 VDC 1,2 W                                                                                          |
| Hastighed       | : | All ports 115.2K bps max                                                                                   |
| Input           | : | Input type : non-isolated On voltage level : +1V max (Connect to GND) Off voltage level : +3.5V~30V (Open) |
| Isolation       | : | No                                                                                                         |
| Output          | : | Output type : Open-collector Output current : 100mA Max load voltage : +30 VDC                             |
| Stik            | : | 14-pin screw terminal block ( accepts 16~22 AWG wires ); 3.5mm pitch                                       |
| Watchdog        | : | Yes                                                                                                        |
| Dimensioner     | : | 123mm x 72mm x 33mm                                                                                        |

