

## 1GHz G-Series T40E Embedded PC Fanless Low Power FEATURES

- G-Series T40E Embedded 1GHz
- 4 GB DDR3L RAM (1 x 8GB max)
- 2 x 10/100/1000 RJ45 LAN
- 4 x USB 2.0
- 1 x RS232/422/485, 1 x RS232/422/485/CANBUS
- 1 x 2.5" SATA drive bay, 1 x CFast™ Socket
- 1 x PCIe Mini-Card
- 1 x VGA, 1 x Display Port. Dual Display
- DC 9V ~ 32V. 46VA
- 10°C ~ 55°C



## SPECIFICATIONS

|                 |   |                                                           |
|-----------------|---|-----------------------------------------------------------|
| CPU             | : | AMD G-Series T40E 1GHz dual-core                          |
| Storage         | : | 1 x 2.5" SATA drive bay, 1 x CFast™ Socket, 1 x SD Socket |
| USB             | : | 4 x USB 2.0                                               |
| Operating Temp. | : | -10°C ~ 55°C (-13°F ~ 122°F)                              |
| Ethernet        | : | 2 x 10/100/1000 RJ45 Ethernet                             |
| GPIO            | : | 2 In, 2 Out                                               |
| Hukommelse      | : | 1 x 4GB DDR3L (1 x 8GB max) 204-Pin SoDIMM                |
| Input           | : | 9V ~ 32V. 46VA Max                                        |
| OS SUPPORT      | : | Windows 7 /8 /8.1, and Linux                              |
| Porte           | : | 1 x RS232/422/485, 1 x RS232/422/485/CANBUS               |
| RAID niveau     | : | 1 x PCIe Mini-Card                                        |
| Skærm           | : | 1 x VGA, 1 x Display Port. Dual Display.                  |





**DANBIT**

EPC-AMD+

## SPECIFICATIONS

Certifications : CE / FCC / RoHS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.