

26 "TFT monitor with 300-nits, Dust and set seal IP54 in the front, IP20 rear, Dual AC / DC

\$6,537.05 tax excluded



Antal farver: 16.7M (8-bit/color)
Certifications: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 10 V
Data: 5, 6, 7, 8
Dimensioner: 621 x 444 x 90 mm
Driftstemperatur: -15 to 55°C (5 to 131°F)
IP-Tæthed: IP54, front IP20, rear
Kontrast: 1500:1, 300 cd/m², 16:10
Opløsning: 1920 x 1200
Porte: RS-232 ports x 1 (DB9 male)
RS-232/422/485 ports x 1, software-selectable (terminal block)
Weight: 12,650 g

Product attributes:

Reference:
MON26-TFT-MD
UPC: 25950

26 "TFT metal monitor, LED backlight, IP54

1920 x 1200

300 nits, 1500:1, 16:10

Response time: 15Ms

Display angle: 176 ° / 160 ° < br> 1 x DVI-D (29-pin DVI-D connectors female)

1 x VGA (15-pin D-sub connector female)

1 x RS232 (DB9 male)

1 x RS232 / 422/485 (software selected terminal block)

Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)

-15 to 55 ° C (5 to 131 ° F)

Desktop, Panel mounting, VESA mounting

CISPR 32, FCC Part 15B Class A

EN 55032/24

621 x 444 x 90 mm

weight: 12,650 g

Optional: RS-232: TxD, RxD , RTS, CTS, DTR, DSR, DCD, GND

Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND

Optional: RS-485-2w: Data +, Data, GND < br> Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND

Product gallery:

