

24 "TFT touch monitor with 300-nits LCD, with single touch, dust and leakproof IP66, Dual AC / DC inputs,



\$8,826.31 tax excluded

Antal farver: 16.7M (8-bit/color)

Certifications: EN 55032/24, CISPR 32, FCC Part 15B Class A, EN 60950-1, IEC 60950-1, UL 60950-1

Dimensioner: 647 x 414 x 95 mm

Driftstemperatur: -15 to 55°C

I/O: 3 x BNC, 2 x DVI-I, 1 x VGA

Installation: Panel montering

Kontrast: 5000:1, 300 cd/m2, 16:9

Compositions: Metal

Pixels: 1920x1080

Porte: RS-232/422/485 ports x 1, software-selectable (terminal block)

Touch: Capacitive touch, 4 points

Weight: 12000 g

Product attributes:

Reference:

MON24-TFT-MD-T

UPC: 25953

24 "TFT monitor LED backlight, IP66

LED backlight

1280 x 1024

350 nits, 5000: 1, 16: 9

Display angle: 178 ° / 178 °

Capacitive 4 points

3 x BNC

1 x DVI-I (29-pin DVI-D connectors female)

1 x VGA (15-pin D-sub connector female)

1 x RS232 / 422/485 (software selected terminal block)

Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)

Panel mounting

-15 to 55 ° C (5 to 131 ° F) < br> CISPR 32, FCC Part 15B Class A

EN 55032/24 for weight: 12000 g

647 x 414 x 95 mm

Optional: RS-232: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND

Optional: RS-485-2w: Data +, Data, GND

Optional: RS -485-4w: Tx +, Tx-, Rx +, Rx-, GND

Product gallery:

