

15 "monitor with 1000-nits LCD with electric without touch, dust and leakproof IP66, Dual AC / DC inputs, FEATURES

24 "TFT metal monitor with capacitive touch, IP66, IP20
LED backlight
1280 x 1024
1000 nits, 700: 1, 4: 3
Display angle: 160 ° / 140 °
1 x DVI-I (29-pin DVI-D connectors female)
1 x VGA (15-pin D-sub connector female)
1 x RS-232 (DB9 male)
1 x Optional RS232 / 422/485
Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)
Desktop, Panel mounting
Weight: 6,100 g
429 x 387 x 75 mm
-40 to 70 ° C
CISPR 32, FCC Part 15B Class A
EN 55032/24
Optional: RS-232: Tx D, Rx D, RTS, CTS, DTR, DSR, DCD, GND < Optional: RS-422: Tx +, Tx -, Rx +, Rx -, GND
Optional: RS-485-2w: Data +, Data, GND
Optional: RS-485-4w: Tx +, Tx -, Rx +, Rx, GND



SPECIFICATIONS

Operating Temp.	:	-40 to 70°C
Antal farver	:	16.7M (8-bit/color)
I/O	:	1 x DVI-D, 1 x VGA
IP-Tæthed	:	IP66, front IP20, rear
Kontrast	:	1000 cd/m2, 700:1, 4:3
Luftfugtighed	:	5 to 95% (non-condensing)
Compositions	:	Metal
Porte	:	RS-232 ports x 1 (DB9 male) RS-232/422/485 ports x 1, software-selectable (terminal block)
Weight	:	6,100 g
Dimensioner	:	429 x 387 x 75 mm
Certifications	:	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V

