

19 "LCD monitor with 300-nits, with multi-touch, dust and leakproof IP66, IP20 rear, dual AC / DC inputs, FEATURES

19 "LCD metal monitor, IP66 front, IP20 back side

1280 x 1024

300 nits

2000: 1, 5: 4

LED backlight

Response time: 20ms

view angle: 178 ° / 178 °

1 x RS-232 (DB9 male)

1 x DVI-D (29-pin DVI-D female)

1 x VGA (15-pin D-sub female)

1 x RS232 / 422/485 (software selectable terminal block)

Capacitive touch (PCAP), 4 Points

Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)

- 15 to 55 ° C (5 to 131 ° F)

429 x 387 x 75 mm

Weight: 7,800 g

RoHS, CRoHS, WEEE

Optional: RS-232: Tx D, Rx D, RTS, CTS, DTR, DSR, DCD, GND

Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND

Optional: RS-485-2w: Data +, Data, GND

Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	1 x DVI-D, 1 x VGA
Kontrast	:	2000:1, 300 cd/m2, 5:4
Porte	:	1 x RS-232, RS-232/422/485 ports x 1, software-selectable (terminal block)
Touch	:	Multi-touch, 4 points
Weight	:	7,800 g
Dimensioner	:	429 x 387 x 75 mm
Certifications	:	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V

