

24 "LCD monitor with 300-nits, capacitive touch, dust and leakproof IP54, IP20 rear, dual AC / DC inputs,



\$4,162.88 tax excluded

Antal farver: 16.7M (8-bit/color)

Certifications: IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V

Driftstemperatur: -15 to 55°C

Forsyning: 100 to 240 VAC, 24 VDC (18 to 30 V)

I/O: 1 x DVI-D, 1 x VGA

Kontrast: 5000:1, 300 cd/m², 16:9

Porte: 1 x RS-232, RS-232/422/485 ports x 1, software-selectable (terminal block)

Touch: Capacitive touch, 4 points

Weight: 9,570 g

Product attributes:

Reference:

MON24-MD-T

UPC: 25959

24 "LCD metal monitor, IP66 front, IP20 rear

1920 x 1080

300 nits, 5000: 1, 16: 9

LED backlight

Response time: 25ms

viewing angle: 178 ° / 178 °

Capacitive touch, 4 points

1 x RS-232 (DB9 male)

1 x DVI-D (29-pin DVI-D female)

1 x VGA (15 -Pin D-sub femlae)

1 x RS232 / 422/485 (software selectable terminal block)

Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)

-15 to 55 ° C (5 to 131 ° F)

595 x 393 x 75 mm & nbsp;

Weight: 9.570 g

Desktop, Panel mounting, VESA mounting

Optional: RS-232: Tx D, Rx D, RTS, CTS, DTR, DSR, DCD, GND

Optional: RS-422: Tx +, Tx -, Rx +, Rx -, GND

Optional: RS-485-2w: Data +, Data, GND

Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND

Product gallery:

