

12" Robust tablet PC, IP66, 1024 x 768, Wifi, resistive touch, 700 nits

FEATURES

- 12" Robust Tablet PC with IP 66
- Intel® Core™ 3955U 2GHz
- 4GB DDR3L RAM, upgradeable to 32GB
- M.2 2280 SSD, SD SLOT
- built-in 3-axis sensor, dual speaker
- 700 nits LED backlight
- Resistive touch, support defroster function
- 9 x programmable button
- 2 x contrast adjustment button
- 2 x sound adjustment button
- 2 x RS232 (COM1 with power), RS-232/422/485
- 2 x USB 2.0 / 3.0, USB 2.0
- 1 x CAN bus (SAE J1939 / OBDI II supported)
- 1 x Audio jack
- Vesa 75/100 mounting
- Power supply 9-60V DC
- Windows 10 IoT Enterprise



SPECIFICATIONS

CPU	:	Intel Celeron 3955U 2GHz
Operating Temp.	:	-30°C to +55°C
bluetooth	:	Bluetooth V4.0 Class 2
Chok/Vibration	:	MIL-STD-810G, 40G at 11ms Terminal / Sawtooth
Harddisk	:	M.2 2280 SSD, SD slot
Hukommelse	:	DDR3L SODIMM, expandable to 32GB
I/O	:	2 x RS232 (COM1 med power), RS-232/422/485 2 x USB 2.0 / 3.0, USB 2.0 1 x CAN bus (SAE J1939 / OBDI II supported) 1 x Audio jackstik
Kontrast	:	700 Nits
Luftfugtighed	:	Humidity 95%, non-condensing
Netværk	:	Gigabit Ethernet (RJ45)
Skærm	:	12.1" XGA TFT LCD with LED backlight (1024 x 768)
Software	:	DashON



SPECIFICATIONS

Touch	:	5-wire Resistive touch. Defroster function
WiFi/WLAN	:	Wi-Fi 802.11 a/b/g/n/ac
Weight	:	4.83 kg, 4.90 kg
Dimensioner	:	325 x 280 x 67 (mm)
Certifications	:	CE, FCC,CB

