

Isolated USB to RS485 converter, -25 ° C ~ +75 ° C FEATURES

- USB to RS485 converter, isolated
- 1 x RS485 7-pin terminal block
- 1 x USB-B
- Speed: 300 ~ 115200 bps
- For USB 1.1 / 2.0 (High Speed)
- 2500 VDC isolation on RS485 side
- To DIN rail mounting
- No external power supply required
- Input +5 VDC from USB port
- OS support WIN 98 / ME / 2000 / XP (32 / 64-bit) / Vista (32/64-bit) / 7 (32/64-bit) / 8 (32/64-bit) / 10 / Linux
- Operating temp. -25 ° C ~ +75 ° C
- USB cable (1.8m) included



SPECIFICATIONS

USB	:	Fully Compliant with the USB 1.1/2.0 (High Speed)
Operating Temp.	:	-25 °C ~ +75 °C
Andet	:	Power and data flow indicator for troubleshooting
Forsyning	:	No External Power Supply required
Hastighed	:	300 ~ 115200 bps
Isolation	:	2500 VDC Isolation Protection on the RS-485 side
Montering	:	Tiny packaging fits on your DIN-Rail
OS SUPPORT	:	Driver Supports Windows 98/ME/2000/XP (32/64-bit)/Vista (32/64-bit)/ 7 (32/64-bit)/8 (32/64-bit)/10/Linux
Stik	:	RS-485: Removable 7-Pin Terminal Block USB: Type B
Dimensioner	:	(W x H x D) 52 mm x 87 mm x 27 mm

