

10.1 "LCD monitor, VGA and HDMI, Full IP66 / IP69K, vandal proof, PCAP multi touch

FEATURES

- 10.1 "LCD screen for 1 x VGA
- 1 x HDMI
- 1 x USB (touch)
- PCAP multitouch (USB)
- Resolution: 1280 x 800 @ 60Hz , 75Hz
- Brightness: 350 nits (cd / m2)
- OSD function
- Contrast: 800: 1
- Full IP66 / 69K and vandal proof
- Operating temp. 0 - +50 C °
- Supply 9-36VDC, 15W
- For VESA75 or panel mounting
- 220 x 300 mm (H x B)



SPECIFICATIONS

Operating Temp.	:	0 - +50C°
Antal farver	:	16.7M Colors
Forsyning	:	1 x AC/DC Power adapter, 9~36V DC or 100~240V AC Power Input (optional)
Interface	:	x VGA (M12 connector) 1 x HDMI (IP66 HDMI connector) U1 x USB for touch (M12 connector) Power Input :1 x 12V DC input (M12 connector)
IP-Tæthed	:	Full-IP66/IP69K
Kontrast	:	800 : 1 (typ.)
Lysstyrke	:	350 nits (cd/m2)
Materiale	:	Stainless Steel
Montering	:	75x 75 VESA Mount. Panel mount for optional
Opløsning	:	1280 x 800 @ 60Hz, 75Hz
OSD	:	5-key OSD buttons • OSD Function : Contrast, Color, Position, Auto-adjustment, Factory Settings
Pixels	:	Pixel Pitch (mm) : 0.2125(H) x 0.21525(V)



SPECIFICATIONS

Strømforbrug	:	15W typical, normal operation
Tilbehør	:	Power Cord : 1 x 1.5m power cord
Touch	:	P-cap multi-touch (USB)
Type	:	10.1" LCD
Dimensioner	:	220 x 300 mm (H x B)

