

Wireless industrial WLAN up to 150Mbps, 2.4GHz,
9-48V DC, extended operating temperature of -40°C
to 75°C

FEATURES

- WLAN up to 150Mbps (Single radio 2.4GHz)
- Industrial 1x1 SISO (Single Input Single Output)
- IEEE 802.11 b/g/n
- 2*10/100Base-TX WAN/LAN Port
- Chipset: Qualcomm/Atheros AR9331 SoC
- Tx Power (EIRP) 21 dB for 2.4GHz
- WPA, WPA2, TKIP, AES
- Power Input: 9~48VDC in 4-Pin Terminal Block
- Reverse Polarity Protection
- IP30 Protection
- DIN-Rail and wall mounting
- Operating temperature: -40° to 75°C
- Weight: 1.0 lbs (approx. 1 kg)
- Dimensions: 26 x 95 x 75 mm



SPECIFICATIONS

Antenne	:	One External SMA Antenna: 3dBi for 2.4GHz (SISO)
Approval	:	EMI, EMS, RF, RF Radiation Exposure, EN60950-1 CNS14336-1, RoHS Compliant
I/O	:	2*10/100BasetT(X), auto negotiation speed, Full/Half Duplex Mode
IP-Tæthed	:	IP30
Luftfugtighed	:	10% to 90%, (non-condensing)
Compositions	:	Metal, IP30 protection
Montering	:	DIN-Rail eller væg montering
Netværk	:	US/TW: 2.412G~2.462GHz EU/AU/NZ: 2.412G~2.472GHz
Protokol	:	IP, TCP, UDP, ARP, BOOTP, ICMP, HTTP, HTTPS, DNS Proxy, NTP, RADIUS, Dynamic DNS, SNMP
Standarder	:	IEEE 802.11 b/g/n IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet
Strømforbrug	:	2 Watts
Strømforsyning	:	9 to 48VDC redundant input



ANR-AMS-2111-T

SPECIFICATIONS

Weight	:	ca 1 KG
Dimensioner	:	26 x 95 x 75 mm
Certifications	:	FCC, CE, NCC, RCM

