

4 port USB 3.1 Gen 2 HUB, 2 x USB-A, 2 x USB-C, 10 Gbit/s DIN mounting

FEATURES

4 port USB 3.1 Gen 2 Hub
2 x Type-A, 2 x Type-C, 1 x Type-C Upstream
For DIN-Rail or Desktop Mount
Supports: 10Gbps (SS +) , 5Gbps (SS), 480Mbps (HS), 12Mbps (FS), 1.5Mbps (LS)
Power supply: + 7 ~ 24VDC (12V, 1A included) via DC plug or terminal block
Power per port: 0.9A at the same time
Backwards compatible with: USB 1.1, 2.0, 3.1 Gen 1
Temperature range: 0 ~ 55 ° C
Humidity: 5 to 95% RH
Dimensions: 151.1 x 62 x 34 mm



SPECIFICATIONS

USB	:	USB 3.1 Gen 2
Andet	:	0,9 A output pr USB downstream port
Kompatibilitet	:	USB 1.1, 2.0, 3.1 Gen 1, Gen 2
LED	:	LED indicator for hver USB port
Luftfugtighed	:	5 to 95% RH
Maks. hastighed	:	10 Gb/s
Montering	:	DIN skinne eller Desktop montering
Porte	:	2 x USB-A, 2 x USB-C, 1 x USB-C (Upstream)
Strømforsyning	:	+7~24VDC (12V, 1A medfølger) via DC stik eller terminal block
Temperatur	:	0 ~ 55° C
Dimensioner	:	151,1 x 62 x 34 mm

