

8-Port Industrial Unmanaged Switch, 2 FTP Ports, FEATURES

- Supporter 6-Port 10 / 100Tx and 2 x Gigabit Combo Ports
- 2 x 10/100 / 1000Tx RJ45
- 2 x 100/1000 SFP Slots
- Supporter Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 8K MAC Address Table
- Surge Protection: 2,000 VDC Support
- ESD Protection: 6,000 VDC Support
- UL Class I, Division 2 Certified
- Redundant Power Input Design: 12 ~ 48VDC
- Built-in 1 x Relay Output for Power Failure Warning
- IP30 Rugged Metal
- Wall and DIN Rail Mounting
- Operating Temperature EOT: -40 ° to 75 ° C



SPECIFICATIONS

Operating Temp.	:	Standard: -10° to 70°C
Approval	:	EMI, EMS, FCC Class A,
Chok/Vibration	:	IEC60068-2-6, IEC60068-2-27
Ethernet	:	6*RJ45 Ports w/10/100Tx , 2 *RJ45 Ports w/10/100/1000TX Ethernet and 2*100/1000 SFP Slot
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5 to 95%, (non-condensing)
Compositions	:	Metal, IP30 beskyttelse
Montering	:	Din skinne og væg montering
Netværk	:	10Base Tx: 2-pair UTP/STP Cat. 3,4,5 100Base Tx: 2-pair UTP/STP Cat. 5 1000Base Tx: 2-pair UTP/STP Cat. 5/5E
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber
Strømforbrug	:	10W



**DANBIT**

ANR-LNX-0802C-SFP

SPECIFICATIONS

Dimensioner : 46 x 99 x 142 mm (W*D*H)

Certifications : FCC, CE, UL 61010-1, UL 61010-2-201, UL Class 1 Division 2, ISA 12.12.01



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.