

10-port industrial unmanaged switch with 2 SFP ports
and 8 RJ45 ports and extended temperature -40 ° to
75 ° C

FEATURES

- 8 x 10/100 / 1000Tx RJ45 for PoE + (30W / port)
- IEEE 802.3at for 2 x 100/1000 SFP ports for Auto MDI / MDI-X Function for Store-and- Forward Switching Architecture
- 20Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC for UL Class I , Division 2 Certified
- Supply Voltage: 48 ~ 55VDC
- Built-in Relay Output for Power Failure for IP30
- Rugged Metal Case Design for DIN Rail and Wall Mounting - Operating Temperature: -40 ° to 75 ° C



SPECIFICATIONS

Operating Temp.	:	EOT: -40° to 75°C
Ethernet	:	8 x RJ45 Ports w/10/100/1000Tx (PSE 30W/Port)
Fiber	:	2 x 100/1000 SFP Slot
Luftfugtighed	:	5% to 95%, (non-condensing)
Compositions	:	Metal IP30 protection
Montering	:	DIN-skinne og væg montering
Netværk	:	10Base Tx: UTP/STP Cat. 3,5 100Base Tx: UTP/STP Cat. 5 1000Base Tx: UTP/STP Cat.5/5e/6
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	210 Watts @ 48V 250 Watts @ 51-55V (Full Load w/ PoE)
Strømforsyning	:	48~55VDC, Redundant Input
Dimensioner	:	46 x 99 x 142 mm



**DANBIT**

ANR-LNP-1002G-SFP-T

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.