

12-Port Gigabit Switch with PoE + unmanaged, 8 x RJ45 ports and 4 x SFP ports, -40 ° to 75 ° C, 48-55VDC

FEATURES

- 8 x 10/100 / 1000Tx RJ45
- PoE+ (30W / port)
- 4 x 100/1000 SFP Ports
- Auto MDI / MDI-X Function
- Store-and-Forward Switching Architecture
- 24Gbps Back-Plane (Switching Fabric)
- 8K MAC Address Table
- 9.6Kbytes Jumbo Frame
- Surge Protection: 2,000 VDC
- ESD Protection: 6,000 VDC
- Supply Voltage: 48 ~ 55VDC
- Built-in Relay Output for Power Failure
- IP30 Rugged Metal Case Design
- DIN Rail and Wall Mounting
- Operating Temperature: -40 ° to 75 ° C



SPECIFICATIONS

Operating Temp.	:	-40° to 75°C
Buffer	:	7,926pps (default)
Chok/Vibration	:	IEC60068-2-32, IEC60068-2-27
Ethernet	:	8*10/100/1000Tx RJ45 (w/8*PSE: 30W/Port)
Fiber	:	4*100/1000 SFP Slot
Forbindelse	:	1 removable 6-contact terminal block
Luftfugtighed	:	5% to 95%, (non-condensing)
Compositions	:	Metal IP30 protection
Protokol	:	CSMA/CD
Standarder	:	IEEE 802.3 10BaseTx Ethernet IEEE 802.3u 100BaseTx Fast Ethernet IEEE 802.3ab 1000BaseTx IEEE 802.3z Gigabit Fiber IEEE 802.3at PoE+
Strømforbrug	:	15 Watts Full load w/PoE 215W@48V / 255W@51~55V
Strømforsyning	:	48-55VDC



**DANBIT**

ANR-LNP-1204G-SFP-T

SPECIFICATIONS

Certifications : FCC, CE, UL 508, UL Class 1 Division 2, ISA 12.12.01



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.