

Wifi bridge, Wifi Uplink, Ethernet/UART to Wi-Fi converter. 3 different interfaces Wifi, Ethernet and UART RS232/485. Roaming

FEATURES

- Wifi Uplink or Ethernet WAN connection
- 1 x LAN port
- 1 x RS232 / RS485 for Modbus RTU
- 1 x Digital input / 1 x Digital output
- Roaming - field strength controlled
- IEEE 802.11a/b/g/n/ac Wi-Fi
- Supply voltage: 9 to 48 VDC
- DIN rail
- Operating temperature -20°C to +60°C
- Dimensions: 131 x 108 x 31 mm



SPECIFICATIONS

Operating Temp.	:	-20 °C to 60 °C
Afstand	:	Op to 50 meters
Antenne	:	5 dBi 2.4/5 GHz
Forbindelse	:	Max. 10 Clients (AP mode)
Indgang	:	1 x DI ("Logic 0": 0~3V, "Logic 1": 3.3V~30V)
Input	:	+9 to 48
Kanaler	:	2.4GHz 1~11 / 5GHz 36/40/44/48/149/153/157/161/165
Montering	:	DIN-Rail
Porte	:	1 x RJ45 / 1 x RJ10
Protokol	:	WEP / WPA / WPA2 / WPA-PSK / WPA2-PSK
Standarder	:	IEEE 802.11a/b/g/n/ac
Udgange	:	1 x DO (Relay Mode, up to 30V / 1A)



**DANBIT**

WLAN-AP-CNV

SPECIFICATIONS



Danbit A/S Værkstedvej 39 Køge, 4600 Denmark



+45 56662020



salg@danbit.dk

For business customers only (B2B). Prices exclude VAT. We reserve the right to correct errors and make changes.