

24 "pcap multi-touch fanless panel PC, 7th Generation Intel® Core Kaby Lake i5-7300U Processor

FEATURES

- Chipset integrated in the processor (SOC)
- Full HD
- 1920 x 1080 resolution
- Pixel: 274,5x274,5
- Contrast: 3000
- Nits: 250
- Front IP65 < br> 2 x 260pin SODIMM socket
- up to 32GB per slot (DDR4 SDRAM 2400) Pattern 2 |
- 1 x 2230 1 x
- mPCIe with SATA or mSATA PCIE x1 | 1 x 2.5 "Drive
- Bay (storage) to 4 x USB 3.0
- 1 x SATA III
- 1 x HDMI Kabel 1 x DisplayPort (DP)
- 2 x RJ45
- Audio chipset: Realtek ALC892
- 10 / 100/1000 Base-Tx GbE Compliant
- Supply Voltage: DC + 19-24V
- Operating temperature: 0-40 degrees
- Weight: 6.9 kg (without battery and adapter)
- Dimensions: 538.6 x 342.6 x 45.2 mm | OS support:
- Win 10 64 bit / Linux



SPECIFICATIONS

Storage	:	1 x 2.5" Drive Bay
Chipset	:	integrated in Processor (SOC)
Operating Temp.	:	0°C ~ 40°C
Batteri	:	Optional Smart Battery Pack 14.4V 6900mAh, 99.4Wh
Chok/Vibration	:	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis, With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
Controller	:	touch controller: EETI EXC84H5680
Ethernet	:	Chipset: 1 x Intel® I211AT, 1 x Intel® I219LM
Forsyning	:	DC in +19V~24V
Hukommelse	:	2 x 260pin SODIMM socket up to 32GB Per Slot DDR4 2400 SDRAM
I/O	:	4 x USB 3.0, 1 x SATA III, 1 x HDMI, 1 x Display port, 1 x RJ45
Kamera	:	5.0M CMOS with auto-focus
Kontrast	:	250 cd/m ² , 3000



SPECIFICATIONS

Luftfugtighed	:	0% ~ 90% Relative Humidity, Non-condensing
Lyd	:	Chipset: Realtek ALC892
Lyskilde	:	LED backlight
Læser	:	Vinkel 89(U), 89(D), 89(L), 89(R)
Montering	:	Optional Mounting Kit (VESA 75 x 75, 100 x 100)
Netværk	:	10/100/1000 Base-Tx GbE compatible
Pixels	:	274.5×274.5
Skærm	:	Monitoring System Temperature & Voltage
Touch	:	Projective Capacitive
Udvidelser	:	1 x M.2 2230 1 x mPCIe with SATA or PCIE x1 mSATA
Watchdog	:	H/W Reset, 1sec. ~ 65535sec. and 1sec./step



SPECIFICATIONS

Weight	:	6.9kg (Uden batteri og adapter)
Dimensioner	:	539.6 x 342.6 x 45.2 mm
Certifications	:	CE : IEC/EN60601-1-2 FCC : Part 15 Class B UL60601-1: AAMI /ANSI ES60601-1:2005/(R)2012 and A1:2012,C1:2009/(R)2012 and A2:2010/(R)2012 CB: IEC 60601-1/A1:2012 & EN 60601-1/A1:2013 (Ed 3.1) EN 60601-1:2006+A11:2011+A1:2013+A12:2014

