

8-port RS-232/422/485 PCI Express serial board FEATURES

- PCI Express 1.0 compliant
- 921.6 kbps maximum baudrate for fast data transmission
- 128-byte FIFO and on-chip H/W, S/W flow control
- Variety of connection cables and boxes available for RS-232/422/485
- Low-profile form factor fits small-sized PCs
- Drivers provided for a broad selection of operating systems, including Windows, Linux, and UNIX
- Easy maintenance with built-in LEDs and management software
- RS-232 :TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
- RS-422 : Tx+, Tx-, Rx+, Rx-, GND
- RS-485-4w : Tx+, Tx-, Rx+, Rx-, GND
- RS-485-2w Data+, Data-, GND



SPECIFICATIONS

Operating Temp.	:	0 to 55°C (32 to 131°F)
Approval	:	EMC EN 55032/35 EMI CISPR 32, FCC Part 15B Class B
Baudrate	:	50 bps to 921.6 kbps (supports non-standard baudrates), Data Bits 5,6,7,8. Stop Bits 1,1.5,2 Parity N,E,O,S,M, FC,N,RTS/CTS,XON/XOFF
FIFO	:	128 bytes
OS SUPPORT	:	DOS95/98/ME/NT/2000/XP/2003/Vista/2008/7/8/8.1/10 (x86/x64),Linux kernel 2.4.x, Linux kernel 2.6.x, Linux kernel 3.x, Linux kernel 4.x, Linux kernel 5.x, UNIX Drivers Solaris 10, UnixWare 7, SCO OpenServer 5, SCO OpenServer 6
Stik	:	VHDCI 68
PCI Express	:	PCI Express 1.0
chip	:	16C550C compatible
Dimensioner	:	68.9 x 88 mm (2.71 x 3.46 in)