

## M-BUS to RS232 / RS422 / RS485 converter, M-BUS slave units can be connected, -25 - +75°C

### FEATURES

RS485 / RS422 / RS232 converter for Meter-Bus meters, actuators, etc.  
Supports up to 100 Meter-Bus meters (slaves)  
Selecting the serial port, only one can be selected to be active  
2 x Baud rate (M-bus and COM port can be selected at different speeds)  
Baud rate: 300 to 115,200 bps  
Transparent data - no protocol conversion  
M-bus connection is 2-wire , max. 350meter.  
larger distance up to 5km requires a number of M-bus repeaters  
Supply voltage: 10 - 30VDC, 1.8 - 12Watt  
Dimensions: 122 x 72 x 33 mm | Removable terminal blocks  
Operating temperature: -25 - + 75 ° C  
DIN bracket  
Robust plastic housing



## SPECIFICATIONS

Baudrate	:	300 - 115.200 COM-port og M-BUS uafhængig
Data	:	Databit: 5,6,7,8 Stop: 1,2 Parity: None, Even, Odd, Space, Mark
Forsyning	:	10 - 30VDC, 1,8 - 12Watt (afhængig af M-BUS enheder)
Interface	:	M-BUS (meter-bus)
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	122 x 72 x 33 mm
Porte	:	RS485 eller RS422 eller RS232