

M-BUS to RS232 / RS422 / RS485 MODBUS Master, 2 x
Baud rate select. M-Bus standard: A-13757, CJ /
T-188, -25 - +60°C

FEATURES

- RS485 / RS422 / RS232 Master Gateway to Meter-Bus Slaves (sensors, actuators, etc.)
- Supports up to 100 Meter-Bus meters (slaves)
- MODBUS RTU function codes: 0x03 and 0x04 readdata
- Selection of serial port, only one can be selected to be active
- Baud rate x 2 (M-bus and COM port can be selected at different speeds)
- Baud rate M-bus: 300-2400 bps
- Baud rate COM port: 300-115200 bps
- Transparent data - no protocol conversion
- M-BUS connection, 2-wire, max. 350meter.
- Greater distance up to 5km requires a number M-bus repeaters
- Supply voltage: 10 - 30VDC, 1.8 - 12Watt
- Dimensions: 122 x 72 x 33 mm
- Removable terminal blocks
- Operating temperature: -25 - + 60°C
- DIN mount
- Robust plastic case



SPECIFICATIONS

Baudrate	:	300 - 115.200 COM-port og M-BUS 300 - 2400 (uafhængig)
Data	:	Support MODBUS RTU - code 0x03 og 0x04 (Meter data)
Forsyning	:	10 - 30VDC, 1,8 - 12Watt (afhængig af M-BUS enheder)
Interface	:	M-BUS (meter-bus) - slaver
Kabinet	:	Plast med DIN-beslag og terminal-blokke
Mål og vægt	:	122 x 72 x 33 mm
Porte	:	RS485 eller RS422 eller RS232 (MODBUS Master)

